

RDO5231E-Z5E

2MP WDR IR Dome Network Camera



- 1/2.8" 2Megapixel Progressive scan STRAVIS™ CMOS
- H.265 & H.264 Triple-stream Encoding
- 50/60fps@1080p(1920x1080)
- Smart Detection supported
- WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 7mm ~ 35mm 5X zoom lens
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 100m
- Micro SD memory, IP67, IK10, PoE+

System Overview

With upgraded H.265 encoding technology, Eco-savvy series brings high efficient video compression capability. It can save bandwidth and storage. Meanwhile, the series features starlight, smart IR technology and intelligent image analysis techniques. This series supports reminder function, meanwhile fully protected from dust and water, certified to IP67 and vandal resistant to IK10 standard.

Functions

ePoE technology

The ePoE technology of Rhodium, designed internally, adopts advanced 2D-PAM3 coding modulation from physical layer, and realizes full duplex transmission over 800 meters at the speed of 10Mbps, or 300 meters at the speed of 100Mbps via Cat 5 or coaxial cable media. Besides, it supports PoE and PoC power supply technology which has greatly simplified construction and wiring. ePoE technology offer a new way to accomplish long distance transmission between IP camera and network switch. It allows more flexible surveillance system design, improves reliability and saves construction and wiring cost.

Starlight Technology

For challenging low-light applications, Rhodium's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.006lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, true WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Intelligent Video System (IVS)

IVS is a built-in video analytic algorithm that delivers intelligent functions to monitor a scene for Tripwire violations, intrusion detection, and abandoned or missing objects. A camera with IVS quickly and accurately responds to monitoring events in a specific area. In addition to scene analytics, the camera supports face detection to quickly capture a face and upload the image to a server. The camera also offers tamper detection by recognizing a dramatic scene change and generating a warning message to inspect the camera.

Protection(IP67, IK10, wide voltage)

The camera allows for $\pm 30\%$ input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), the camera is the choice for installation in even the most unforgiving environments.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

RDO5231E-Z5E

2MP WDR IR Dome Network Camera

Technical Specification

Camera						
Image Sensor	1/2.8" 2Megapixel progressive scan CMOS					
Effective Pixels	1920(H) x 1080(V)					
RAM/ROM	256MB/32MB					
Scanning System	Progressive					
Minimum Illumination	0.006Lux/F1.4 (Color,1/3s,30IRE) 0.05Lux/F1.4 (Color,1/30s,30IRE) 0Lux/F1.4 (IR on)					
S/N Ratio	More than 50dB					
IR Distance	Distance up to 100m (328ft)					
IR On/Off Control	Auto/Manual					
IR LEDs	3					
Lens						
Lens Type	Motorized/ Auto Iris(HALL)					
Mount Type	Board-in					
Focal Length	7mm~35mm					
Max. Aperture	F1.4					
Angle of View	H:35° ~ 12°, V:19° ~ 7°					
Optical Zoom	5x					
Focus Control	Motorized					
Close Focus Distance	0.6m					
DORI Distance	Lens	Detect	Observe	Recognize	Identify	
	W	131m(429ft)	52m(170ft)	26m(85ft)	13m(42ft)	
	T	427m(1400ft)	171m(561ft)	85m(278ft)	42m(138ft)	
Pan/Tilt Range						
Pan/Tilt Range	Pan:0°~355°; Tilt:0°~65°; Rotation:0°~355°					
Intelligence						
IVS	Tripwire, Intrusion, Object Abandoned/Missing					
Advanced Intelligent Functions	Face Detection					
Video						
Compression	H.265+ / H.265 / H.264+ / H.264					
Streaming Capability	3 Streams					
Resolution	1080P(1920x1080)/1.3M(1280x960)/ 720P(1280 x 720)/D1(704 x 576/704 x 480)/ VGA(640 x 480)/CIF(352 x 288/352 x 240)					
Frame Rate	Main Stream	1080P(1~50/60fps)				
	Sub Stream 1	D1(1~50/60fps)				
	Sub Stream 2	1080P(1~25/30fps)				
Bit Rate Control	CBR/VBR					
Bit Rate	H.264: 24~9472Kbps H.265: 14~5632Kbps					
Day/Night	Auto(ICR) / Color / B/W					
BLC Mode	BLC / HLC / WDR(120dB)					

White Balance	Auto/Manual/Street Lamp/Outdoor/Manual
Gain Control	Auto / Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Electronic Image Stabilization (EIS)	N/A
Smart IR	Support
Defog	N/A
Digital Zoom	16x
Flip	0°/90°/180°/270°
Mirror	Off/On
Privacy Masking	Off / On (4 Area, Rectangle)
Audio	
Compression	G.711a/ G.711Mu/ AAC/ G.726
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP
Interoperability	ONVIF, PSIA, CGI
Streaming Method	Unicast / Multicast
Max. User Access	10 users / 20 users
Edge Storage	NAS (Network Attached Storage), Local PC for instant recording, Micro SD card 128GB
Web Viewer	IE/Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, Easy4ip
Smart Phone	IOS, Android
Certifications	
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B
Interface	
Video Interface	1 Port(For adjustment only)
Audio Interface	1/1 channel in/out
RS485	N/A
Alarm	1 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC
Electrical	
Power Supply	DC12V, AC24V, PoE+(802.3at)(Class 4)
Power Consumption	<15W

RDO5231E-Z5E

2MP WDR IR Dome Network Camera

Environmental

Operating Conditions	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 95% RH
Storage Conditions	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10

Construction


Casing	Metal
Dimensions	Φ159.1(mm) x 117.9(mm) (6.26" x 4.64")
Net Weight	0.95kg(2.09lb)
Gross Weight	1.20kg (2.65lb)

Ordering Information

Type	Part Number	Description
2MP Camera	RDO5231EP-Z5E	2MP IR Dome Network Camera, WDR, PAL
	RDO5231EN-Z5E	2MP IR Dome Network Camera, WDR, NTSC
Accessories(optional)	PFA138	Junction Box
	PFB302S	Wall mount
	PFB201C	In-ceiling mount
	PFB300C	Ceiling mount
	PFA152-E	Pole mount
	PFA101	Mount adapter
	LR1002	ePoE Over Coax Converter

Accessories

Optional:



Dimensions (mm/inch)

