

RDO82041-B360

4x5MP AI Multi-sensor No-splicing Panoramic Dome Network Camera



- 4x5MP 1/2.7" CMOS image sensor, low illuminance, high image definition
- 4-ch stream output and each channel can output max. 5MP (2592 × 1944) @25/30 fps
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Support 4-channel 120dB WDR
- The intelligent functions of 4 channels can be enabled at the same time
- Intelligent detection: Tripwire, intrusion, fast moving (the three functions support the classification and accurate detection of vehicle and human), abandoned object, missing object, loitering detection, people gathering, parking detection, and face detection
- FlexStream: The 4 channels of images can be viewed in a defined channel with 1 channel stream. That is, the multiple images can be displayed in 1 channel.
- Web5.0 interface design, which is friendly to users, and easy for operation
- Built-in efficient IR LED illuminator and the max. illumination distance is 30 m
- Alarm: 3 in, 2 out; audio: 1 in, 1 out; 485; supports max. 256 G Micro SD card
- 12V DC/POE power supply; 12V power output, and max. current 165mA; easy for installation
- IP67, IK10 protection

AI is a full portfolio of solutions composed of project-oriented products including IPC, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, AI provides precise, reliable and comprehensive AI solutions for verticals.

System Overview

The non-splicing camera can adjust each lens to realize 360° surveillance, which can be used in the scenes with multiple cameras, and is easy to install. Stereo vision camera has the functions such as deep detection and behavior analysis.

Functions

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

Perimeter Protection

With deep learning algorithm, Perimeter Protection technology can recognize human and vehicle accurately. In restricted area (such as pedestrian area and vehicle area), the false alarms of intelligent detection based on target type (such as tripwire, intrusion, fast moving, parking detection, loitering detection and gathering detection) are largely reduced.

Face Detection

Face Detection technology can detect the face in the image. With deep learning algorithm, the technology supports detecting, tracking, capturing and selecting the best face image, and then outputs face snapshot.

One IP Address for Multiple Streams

With one IP address, multi-sensor camera can display multiple images. The camera can do multi-image monitoring through software platform or NVR.

WDR

With advanced Wide Dynamic Range 120dB WDR technology, this network camera provides clear details in the environment of strong brightness contrast. The bright and dark area can get clear video even in high brightness environment or with backlight shadow.

Protection (IP67, IK10, wide voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can work normal after soaking in 1 m deep water for 30 minutes.

IK10: The enclosure can stand the punch more than 5 times from a 5 kg hammer falling from a height of 40 cm (Impact energy is 20J).

Wide voltage: The camera allows ±30% (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

RDO82041-B360

4x5MP AI Multi-sensor No-splicing Panoramic Dome Network Camera

Technical Specification

Camera					
Image Sensor	1/2.7" 5Megapixel Progressive CMOS				
Effective Pixels	2592(H) x 1944(V)				
ROM	32GB				
RAM	4GB				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual 1/3s ~ 1/100,000s				
Minimum Illumination	0.005Lux@F1.7				
S/N Ratio	>56dB				
Illumination Distance	30m (98ft) (IR LED)				
Illuminator On/Off Control	Auto / Manual				
Illuminator LEDs	8 (IR LED)				
Pan / Tilt / Rotation Range	Pan: 0°-360° Tilt: 0°-80° Rotation: 0°-355°				
Lens					
Lens Type	Motorized vari-focal				
Mount Type	φ14				
Focal Length	2.8 - 12mm				
Max. Aperture	F1.7				
Field of View	Horizontal: 100°-36° Vertical: 74°-27° Diagonal: 133°-45°				
Iris Type	Fixed				
Close Focus Distance	0.8mm (2.6ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	Wide	66m (216.5ft)	26.4m (86.6ft)	13.2m (43.3ft)	6.6m (21.7ft)
	Tele	140.4m (460.6ft)	56.1m (184.1ft)	28m (91.9ft)	14m (45.9ft)
Smart Event					
IVS	Abandoned object; missing object				
Professional, Intelligence					
IVS (Perimeter Protection)	Tripwire; intrusion; fast moving (the three functions support the classification and accurate detection of vehicle and human); loitering detection; people gathering; parking detection				
Face Detection	Face detection; track; optimization; snapshot; report high quality picture; face enhancement; face exposure; face attribute extract, 6 attributes and 8 expressions: Gender, age, glasses, expressions (anger, calm, happiness, sadness, disgust, surprise, confusion and fear), mask, beard; face matting setting: face, single inch photo; three snapshot methods: real-time snapshot, optimization snapshot, quality priority; face angle filter; optimization time setting				
Intelligent Search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos.				

Video

Video Compression	H.265; H.264; H.264H; H.264B; MJPEG (only supported stream)
Smart Codec	Smart H.265+/Smart H.264+
Video Frame Rate	Single Stream: Main stream: 5MP (1-25/30 fps) Sub stream: D1 (1-25/30 fps) Third stream: 2MP (1-25/30 fps) FlexStream: Main stream: 2MP (1-25/30 fps) Sub stream: D1 (1-25/30 fps) Third stream: 8MP (1-25/30 fps)
Streaming Capability	3 Streams
Resolution	Single Stream: 5M(2592x1944); 4M(2688x1520); 3M(2048x1536); 2M(1920x1080); 720P(1280x720); D1(704x 576/704x480); CIF(352x288/352x240) FlexStream: 8M(3296x2472); 5M(2592x1944); 2M(1600x1200); 1.3M(1280x960); D1(704x 576/704x480); CIF(352x288/352x240)
Bit Rate Control	CBR/VBR
Video Bit Rate	H.264: 3K - 19456Kbps H.265: 3K - 19456Kbps
Day/Night	Auto (ICR)/Color/B/W
BLC	Yes
HLC	Yes
WDR	4 x 120dB
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom
Gain Control	Auto/Manual
Noise Reduction	3DNR
Motion Detection	Off / On (4 areas, Rectangular)
Region of Interest	Yes (4 areas)
Smart Illumination	N/A
Image Rotation	0° / 90° / 180° / 270° (Support 90°/270° with 1080p resolution and lower)
Mirror	Yes
Privacy Masking	4 areas

Audio

Audio Compression	G.711a; G.711Mu; PCM; G.726; G.723
-------------------	------------------------------------

Alarm

Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; intrusion; tripwire; fast moving; abandoned object; missing object; loitering detection; people gathering; parking detection; scene changing; audio detection; voltage detection; defocus detection; external alarm; face detection; safety exception; voltage detection
-------------	--

Network

Ethernet	RJ-45 (100/1000Base-T)
SDK & API	Yes

RDO82041-B360

4x5MP AI Multi-sensor No-splicing Panoramic Dome Network Camera

Protocol	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; 802.1x; SNMP
Interoperability	ONVIF(Profile S/Profile G/Profile T); CGI; Milestone; Genetec; RTMP; P2P
Storage	FTP; SFTP; Micro SD card (support max. 256 G); NAS
Browser	IE: IE9 and later Chrome: 41.0 and later No-plug version: Safari and edge
Mobile Phone	iOS, Android
Certification	
Certification	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
Port	
RS-485	1 (baud rate range: 1200 bps–115200 bps)
Audio Input	1 channel (RCA port)
Audio Output	1 channel (RCA port)
Alarm Input	3 channel in: 5mA 3V–5V DC
Alarm Output	2 channel out: 300mA 12V DC
Power	
Power Supply	12VDC/PoE (802.3at)
Power Consumption	Basic power consumption: 8.1W (12V DC); 9W (PoE) Max. power consumption (ICR + IR intensity): 21.5W (12V DC); 22.2W (POE+)
Environment	
Operating Conditions	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 95% RH
Storage Conditions	-30°C ~ +60°C (-22°F ~ +140°F)
Protection Grade	IP67; IK10
Structure	
Casing	Metal + Plastic
Dimensions	286.1mm × 111.3mm (11.3" × 4.4")
Net Weight	2.75Kg (8.9lb)
Gross Weight	4.5Kg (11.0lb)

Accessories

Optional:



RPFB303W
Wall Mount



RPFB300C
Ceiling Mount



RPFA111
Mount Adapter



Ceiling Mount

Wall Mount

Ceiling Mount

RPFB303W + RPFA111

RPFB300C + RPFA111



Dimensions (mm[inch])

