

RPZ8655VDR-Z30



Key Features

1. 1/2.8" STARVIS™ CMOS
2. Max. 25/30fps@2592×1944
3. 30x optical zoom and 16x digital zoom
4. Supports detection and capture of faces, humans, and vehicles, along with smoke and flame detection.
5. Supports intelligent analysis for intrusion, single / double line crossing, loitering, wrong-way detection, illegal parking, smart motion detection, and people counting
6. Auto tracking and perimeter protection based on deep learning
7. True WDR, 3D DNR, ICR, Defog and EIS
8. Smart IR distance up to 200m
9. IP66, IK10

RPZ8655VDR-Z30

Specifications	
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Max Resolution	2592(H) × 1944(V)
Electronic Shutter	Auto/Manual, 1/5 to 1/20,000s
Minimum Illumination	Color: 0.005Lux @ (F1.6, AGC ON); B/W: 0.001 Lux @ (F1.6, AGC ON), 0 Lux with IR
Day & Night	Auto (ICR)
Wide Dynamic Range	120dB True WDR
Lens	
Focal Length	5.3 to 159mm
Max Aperture	F1.6 to F4.4
Angle of View	H: 56.8° to 2.6°, V: 42.7° to 2.0°
Optical Zoom	30x
Digital Zoom	16x
Iris Control	Auto/Manual
Focus Control	Auto/Manual/Semi-automatic
DORI Distance	
Detect	103 to 3,090m (337.93 to 10,137.8ft)
Observe	41.2 to 1,236m (135.17 to 4,055.1ft)
Recognize	20.6 to 618m (67.59 to 2,027.6ft)

RPZ8655VDR-Z30

Image

Image Adjustment	Brightness, Sharpness, Contrast, Saturation adjustable
Scene Mode	Indoor, Outdoor, Mirror
Exposure Mode	Auto, Manual, Shutter priority, Iris priority
White Balance	Auto, Tungsten, Fluorescent, Daylight, Shadow, Manual
Day/Night Setting	Auto, Day, Night, Time
Noise Reduction	2D/3D DNR
Image Enhancement	HLC, BLC, Defog, WDR, Anti-shake
Privacy Masking	Support 40 zones, mask color configurable

Event

Alarm Triggers	IVS, Motion detection, Alarm input, Network alarm, Disk alarm, Abnormal sound detection
Alarm Events	Alarm record, Alarm output, FTP upload, SMTP upload, Audible alarm output


Network

Protocols	IPv4/IPv6, HTTP/HTTPS, DNS, DDNS, DHCP, PPPoE, RTSP/ RTCP/RTP, TCP/UDP, NTP, ARP, UPnP, FTP, SMTP, QoS, ICMP, IGMP, SMTP, 802.1x, SNMP, Multicast
Interoperability	ONVIF (Profile S/T/G/M), SDK, CGI
Max Concurrent Streams	10 channels
User/Host Level	Up to 10 users, 3 levels: Administrator, Operator, Media user
Security	IP address filter, encrypted HTTPS, Illegal login lock, IEEE 802.1x
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge

Interface

RPZ8655VDR-Z30

Dimensions (mm)



Accessories

Optional:



RCBK506B
Wall Bracket



RBK348A
Ceiling Bracket



RBK605
Corner Mount



RBK604B
Pole Mount



RBK367
Junction Box



RBK358
Corner Mount



RBK359
Pole Mount